

THP 751 W/IX/I

12NC/Fx: F100656

GTIN (EAN) code: 8050147006566

| DIMENSION | | MEASURE |
|--|--------------|---------|
| APPLIANCE | | |
| Product width | 730 | mm |
| Product depth | 510 | mm |
| Radius of product corner | 10 | mm |
| Product height (MAX protrusion from the worktop) | 58 | mm |
| Underneath the bearing area of the appliance | 38 | mm |
| Distance between cut out and top frontal projection | 11 | mm |
| Distance between cut out and top lateral projection | 85 | mm |
| Plateau thickness | 13 | mm |
| Gas outlet positioning | Rear left | |
| Gas outlet X positioning | 106 | mm |
| Gas outlet Y positioning | 21 | mm |
| Power cable | With product | |
| Power cable positioning | Rear | |
| CUT OUT | | |
| MIN front distance from cut-out to end worktop | 0 | mm |
| MIN rear distance from cut out to wall/furniture | 55 | mm |
| MIN lateral distance from cut out to wall/furniture | 185 | mm |
| MIN height from worktop to above furniture | 420 | mm |
| MIN cut out width | 560 | mm |
| MAX cut out width | 562 | mm |
| MIN cut out depth | 480 | mm |
| MAX cut out depth | 482 | mm |
| MIN cut out radius | 6.5 | mm |
| MAX cut out radius | 8 | mm |
| FLUSH INSTALLATION | | |
| Indicates whether a flush installation is possible. Default is "N" | No | |
| MIN Milling rabbet width | 0 | mm |
| MAX Milling rabbet width | 0 | mm |
| MIN Milling rabbet depth | 0 | mm |
| MAX Milling rabbet depth | 0 | mm |
| Milling rabbet thickness | 0 | mm |
| Radius milling rabbet | 0 | mm |
| Flush installation KIT (2) | N/A | |
| Indicates the minum worktop thickness with standard installation for gas | 20 | mm |
| Indicates the maximum worktop thickness with standard installation for gas | 60 | mm |
| Indicates the minum worktop thickness with flush installation for gas | 0 | mm |
| Indicates the maximum worktop thickness with flush installation for gas | 0 | mm |
| WITH OVEN | | |
| Indicates whether the cooktop can be installed above oven. Default is "Y" | Yes | |
| MIN worktop thickness with oven | 0 | mm |
| MAX worktop thickness with oven | 0 | mm |

| DIMENSION | | MEASURE |
|---|-----------------|-----------------|
| Indicates whether a protection tray against heat or contact is needed with oven. Default is "N" | No | |
| Indicates whether a ventilation opening in the back side of cabinet is needed or not with oven. Default is "Y" | No | |
| Indicates the position of the opening in the back side of the cabinet with oven | N/A | |
| MIN Width of rear opening required with oven | 0 | mm |
| MIN Depth of rear opening required with oven. | 0 | mm |
| MIN AREA of rear opening required with oven | 0 | cm² |
| MIN distance from cabinet to rear wall, with oven | 0 | mm |
| Indicates whether a ventilation opening in the top front side of cabinet is needed or not with oven. Default is "N" | No | |
| MIN Frontal gap required, with oven (2) | 0 | mm |
| MIN frontal opening area required with oven | 0 | cm ² |
| WITH CABINET | | |
| MIN worktop thickness with cabinet | 0 | mm |
| MAX worktop thickness with cabinet | 0 | mm |
| Indicates whether a protection tray against heat or contact is needed. Default is "Y" | Yes | |
| MIN distance from bottom line of appliance to protection tray | 20 | mm |
| Indicates whether a ventilation opening in the tray is needed or not with cabinet | No | |
| Recess dimension X | 0 | mm |
| Recess dimension Y | 0 | mm |
| Positioning dimension X by axis | 0 | mm |
| Distance of the tray from the back panel/wall | 0 | mm |
| Indicates whether a divider is available | N/A | |
| Indicates whether a ventilation opening in the back side of cabinet is needed or not. Default is "Y" | No | |
| Indicates the position of the opening in the back side of the cabinet. | N/A | |
| MIN Width of rear opening of the cabinet | 0 | mm |
| MIN Depth of rear opening of the cabinet | 0 | mm |
| MIN AREA of rear opening of the cabinet | 0 | cm ² |
| MIN distance from cabinet to rear wall | 0 | mm |
| Indicates whether a ventilation opening in the top front side of cabinet is needed or not. Default is "N" | No | |
| MIN Frontal gap of the cabinet | 0 | mm |
| MIN frontal opening area of the cabinet | 0 | cm² |
| INSTALLATION SPACE | | |
| Depth of immersion underneath the appliance | 6 | mm |
| Width protruding area below bottom box | 80 | mm |
| Depth protruding area below bottom box | 83 | mm |
| Protruding area: X positioning | 2 | mm |
| Protruding area: Y positioning | 6 | mm |
| ACCESSORIES FOR INSTALLATION | | |
| Gasket | Separate KIT | |

DIMENSION MEASURE

| Clips | Separate KIT | |
|---|-----------------|----|
| Injector KIT | Separate KIT | |
| Elbow KIT | N/A | |
| COOKTOP HOOD INSTALLATION ONLY FOR GAS | | |
| MIN distance from cooktop to above furniture | 750 | mm |
| MIN distance between cabinets above the cooktop | 600 | mm |
| MAX distance between cabinets above the cooktop | 750 | mm |
| | | |