




PF		
S	Falmec Lab	
M	Evolution - Built-in - 120 cm - Black - 600 m3/h	
AEC	69.8	kWh/a
EEC	B	
FDE	23.2	
FDEC	B	
LE	31.4	
LEC	A	
GFE	80	
GFEC	C	
Qmin	240	m³ /h
Qmax	580	m³ /h
Qboost	580	m³ /h
SPEmin	47	dBa
SPEmax	56	dBa
SPEboost		
PO		
PS	0	W
PI		
F	1	
EEL	69	
Qbep	360	m³ /h
Pbep	337	Pa
Qboost	580	m³ /h
Wbep	145	W
WL	8.6	W
Emiddle	270	lux
Lwa-SPEmax	65	dBa

PF_Scheda prodotto conforme a 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / P0_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps).

PI_Additional information according to 66/2014 Calculation methods: EN 61591:2020 F_Time increase factor / EEL_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximum air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.